

Evo disc golf platforms operating and safety instructions

Versio 1.0

Applicable products:: Evo 2.1, Evo 2.2, Evo 3.2, Evo 4.2

Evo disc golf platforms are safe and durable solution for frisbee golf use. Module based solution is fast to install and, due to its adjustability, is suitable for installation mostly without groundworks. Safety features include; large enough size, straightness, durability, clear visual perceptibility. In addition, the platforms have been raised off the ground, allowing rainwater to drain away and the substrate to dry quickly, resulting in even friction on the platform.



Disc golf platforms are delivered as modules and each model is assembled according to separate installation instructions. In the installation, it is necessary to ensure sufficient load-bearing capacity of the ground so that the throwing platform can be firmly secured against the ground. The platform is installed directly against the ground and this should be taken into account in the shaping of the soil base, so that the platform can be installed horizontally. If necessary, under the platform can be removed from the soil. During the installation, you must try to keep the height of the throwing platform from the ground small and the recommendation is not to aim for a height of more than 30 cm when using a separate support structure. Sand (roughness 0.5-1.6mm) 25kg / module should be installed on the artificial turf of the platform.

Conditions for safe use:

- 1. Platform may only be used by one person at a time.
- 2. The platform is securely installed.
- 3. The platform is horizontal.
- 4. The artificial turf is in good condition and proper sand has been added.
- 5. There is no extra stuff on the platform.
- 6. The platform is clear from ice and dry enough.
- 7. Module frame and deck must be intact and straight.

1. The platform MUST NOT be used if:

- 1. The artificial turf is damaged or partially missing.
- 2. The platform is uneven or unstable.
- 3. The platform is slippery.
- 4. The platform modules are disconnected.
- 5. There is some damage to the module frame or deck.

Platforms should be inspected once a year to make sure;

- 1. The artificial turf carpet is in good condition and sanded.
- 2. The modules are attached to each other and the screws are tightened.
- 3. The platform is firmly against the ground.

Adjusting the platform

The platform can be adjusted if necessary by adding or removing soil from under the platform. It is also possible to use a separate support structure when the support is max every 100cm.

SONES OY – FLATPAD.FI Järvenpääntie 69, 91910, Tupos, Finland, info@flatpad.fi